

RYLARD

www.RylardBoats.com

Technical Data Sheet

PRODUCT NAME: **FAST DRY SEALER/LACQUER FOR SOLID & VENEERED TIMBERS**

CODE NUMBER: **30028**

PRODUCT DESCRIPTION: High quality 1 pack N/C based satin finish sealer/lacquer for solid timbers and veneered MDF and particle boards. Rapid drying allows dust free finishes in un-ideal application conditions.

PERFORMANCE/USE: Combination product that allows a single use material as sealer on bare timbers and as a finish with a satin appearance. Exhibits excellent sanding properties when used as a sealer to allow fast de-nibbing without scratching using 280/320 grit paper. Used by spray application typically on lining out boards for the interior of narrow boats and cruisers.

SURFACE PREPARATION: Pre-sand timbers and veneers with 120/180 grit papers. Ensure surfaces are dust free

APPLICATION: Apply by spray; conventional; HVLP or compliant. Use at supply viscosity; can be thinned if required with up to 10% 18802 thinner

DRYING/CURING: **Air Dry:** Touch Dry 10-15 mins;
Hard dry for packing/overcoating: 30-40 minutes

PHYSICAL PROPERTIES:

Supply Viscosity	30-35 seconds/BS.B4 cup /23°C
Supply SG	0.900 +/- 0.015
Supply Solids:	20%
Gloss:	Satin(20-25% on 60° head)
Theoretical Coverage:	10-12 square metres per litre per coat
VOC Content:	735 grammes per litre
Flash Point / Class / UN No	≤21°C / II / UN 1263
Pack Size	5 litre & 20 litre containers
Shelf Life	12 months unopened, stored at UK ambient temperatures.
Health & Safety:	Refer to Product Safety Data Sheet before use.

This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department

Distributed by:

Mainline
2 Sefton Road
Litherland
Liverpool L21 7PG
Tel: 0151 920 6451
Fax: 0151 920 6452

Your Local Stockist: